



**DO NOT FASTEN PANEL ENDS TOGETHER. DOING SO WILL CAUSE DEFORMATION IN PANEL FACE.**

**NOTE:** 300C PANEL ENDS MUST BUTT AT FACTORY PANEL ENDS AND PANELS CANNOT BE SPLICED. PANEL ENDS CAN ONLY BE FIELD CUT AT PERIMETERS WHERE TRIMS ARE USED FOR TERMINATIONS. PANEL SPLICES ARE NOT REQUIRED NOR AVAILABLE.

**ISOMETRIC VIEW OF FACTORY PANEL ENDS AT JOINT**  
\*CARRIERS NOT SHOWN FOR CLARITY

**INTERIOR INSTALLATION**



5015 Oakbrook Parkway, Suite 100  
Norcross, GA 30093  
T 800.366.4327  
F 770.806.0214  
HDarchitectural.com

*All rights reserved. This drawing is the property of Hunter Douglas. It may not be copied or multiplied, neither wholly nor partly. It may not be submitted for perusal to third parties.*

**SPECIFICATIONS**  
(unless noted otherwise)

MATERIAL: .028" ALUMINUM 300C PANEL | .040" ALUMINUM 300C CARRIER  
FINISH: PAINT | POWDER COAT | DECORATED WOOD FINISH | WOOD VENEER | LUXACOTE  
PERFORATION: NON-PERFORATED | #160

**PANEL BUTT JOINT**

PROJECT: 300C PRODUCT SPECIFICATIONS  
DRAWING NUMBER: 300C-A1.4  
SCALE: 3" = 1'-0"  
DRAWN BY: HDA ENGINEERING  
DATE: 6/28/18