



4'-6" MAX CARRIER SPACING ALLOWABLE AT FIXTURES, TYP.

FIXTURE TO BE INDEPENDENTLY
SUPPORTED BY OTHERS

FIXTURE WITH TRIM FLANGE REQUIRED, BY
OTHERS, NOT BY HUNTER DOUGLAS

SECTION 'B' - 'B'

NOTE: ROUND OPENINGS LESS THAN EIGHT (8) INCHES DIAMETER TYPICALLY FIELD CUT INTO PANEL FACE, TRIM FOR ALL FIXTURES BY OTHERS NOT BY HUNTER DOUGLAS



SECTION 'A' - 'A'

5015 Oakbrook Parkway, Suite 100 Norcross, GA 30093 T 800.366.4327 F 770.806.0214 HDarchitectural.com All rights reserved. This drawing is the property of Hunter Douglas. It may not be copied or multiplied, neither wholly nor partly. It may not be submitted for perusal to third parties.

SPECIFICATIONS

nless noted otherwise)

MATERIAL: .028" ALUMINUM 300C PANEL | .040" ALUMINUM 300C CARRIER
FINISH: PAINT | POWDER COAT | DECORATED WOOD FINISH | WOOD VENEER |
LUXACOTE

PERFORATION: NON-PERFORATED | #160

FIELD CUT PANEL FOR FIXTURE OPENINGS

PROJECT: 300C PRODUCT SPECIFICATIONS DRAWING NUMBER: 300C-A1.9

SCALE: 3" = 1'-0"

DRAWN BY: HDA ENGINEERING

DATE: 6/28/18