



LATERAL BRACING: BRACE WITH HANGER WIRES AND STRUTS PER ASTM E-580 AND IN ACCORDANCE WITH LOCAL CODE REQUIREMENTS.

(4) #12 GAUGE WIRES SPLAYED 90° FROM EACH OTHER AT ANGLE NOT EXCEEDING 45° FROM PLANE OF CEILING. A STRUT FASTENED TO MAIN RUNNER SHALL BE EXTENDED TO AND FASTENED TO STRUCTURE ABOVE. SPLAYED WIRE AND STRUT BRACING TO BE PLACED NOT MORE THAN 12 FEET ON CENTER IN EACH DIRECTION, WITH THE FIRST POINT WITHIN 6 FEET FROM EACH WALL.

**INTERIOR INSTALLATION**



5015 Oakbrook Parkway, Suite 100  
 Norcross, GA 30093  
 T 800.366.4327  
 F 770.806.0214  
 HDarchitectural.com

*All rights reserved. This drawing is the property of Hunter Douglas. It may not be copied or multiplied, neither wholly nor partly. It may not be submitted for perusal to third parties.*

**SPECIFICATIONS**  
 (unless noted otherwise)

MATERIAL: .032" | .040" | .050" | .063" ALUMINUM HOOK-ON PANEL | 18 GA GALV.  
 STEEL 'Z' PROFILE SECONDARY CARRIER  
 FINISH: PAINT | POWDER COAT | LUXACOTE  
 PERFORATION: SEE DETAIL A1.1 THIS SET

**SEISMIC SPECIFICATIONS**

PROJECT: HOOK-ON PRODUCT SPECIFICATIONS  
 DRAWING NUMBER: HOOKON-A1.10  
 SCALE: AS SHOWN  
 DRAWN BY: HDA ENGINEERING  
 DATE: 8/15/16