



① INSERT TWIST CLIP ONTO MAIN TEE AND ROTATE INTO POSITION

② INSERT HANGER BRACKET ONTO TWIST CLIP THREADS

③ ADJUST HANGER BRACKET TO FINAL POSITION AND SECURE WITH 1/4"-20 NYLOCK NUT

④ FLEX TAVOLA BEAM SIDES OVER HANGER BRACKET AND SECURE WITH (2) TWO MIN #6 FASTENERS

INTERIOR INSTALLATION

HunterDouglasContract

CEILINGS

5015 Oakbrook Parkway, Suite 100
 Norcross, GA 30093
 800-366-4327 / 770-806-9557
 fax: 770-806-0214

All rights reserved. This drawing is the property of Hunter Douglas and may not be copied or multiplied neither wholly nor partly. It may not be submitted for perusal to third parties either.

www.hunterdouglascontract.com

SPECIFICATIONS
 (unless noted otherwise)

MATERIAL: .032 ALUMINUM
 FINISHES: PAINT / POWDER COAT / DECORATED WOOD FINISH / WOOD VENEER
 PERFORATION: NON-PERFORATED / CONTACT HD FOR AVAILABLE PERFS

TOLERANCES
 (unless noted otherwise)

DECIMAL: .0 +/- .060
 .00 +/- .030
 .000 +/- .010
 FRACTIONAL: +/- 1/32"
 ANGULAR: +/- 1/2° (.5°)



HANGER BRACKET INSTALLATION

PROJECT: TAVOLA CANTED BEAM PRODUCT SPECIFICATIONS
 DRAWING NUMBER: TAVOCANT-A1.4
 PART NUMBER: N/A
 SCALE: NTS
 DATE: 11/25/14
 DRAWN BY: HDAP ENGINEERING