

VERTICAL SUPPORT SPECIFICATIONS
SEE DETAIL A1.4

HEARTFELT CARRIER
SEE DETAIL A1.3

12" MAX
CARRIER OVERHANG, TYP.

48" MAX VERTICAL SUPPORT SPACING, TYP.

SUSPENSION SPECIFICATIONS
SEE DETAIL A1.2

3⁹/₁₆" SYSTEM DEPTH

12 GA HANGER WIRE
BY OTHERS, TYP.

HEARTFELT HANGER
ASSEMBLY

2-3/8" HEARTFELT
CARRIER*

HEARTFELT PANEL

1⁹/₁₆"

13"
16 REVEAL

2³/₈" MODULE*

TYPICAL SYSTEM SECTION
SCALE: 3" = 1'-0"

PERIMETER CONDITIONS
SEE DETAIL A1.5

FIXTURE RECOMMENDATIONS
SEE DETAIL A1.6

48" MAX CARRIER SPACING, TYP.
6" MAX PANEL OVERHANG, TYP.

13/16" REVEAL

1-9/16"
2-3/8" MODULE*

HEARTFELT PANEL
SEE DETAIL A1.1

NOTE:
HUNTER DOUGLAS ARCHITECTURAL
RECOMMENDS INSTALLING PANELS
WITH RANDOM STAGGERED SEAMS.

NOTE:
GIVEN THE UNIQUE AND SPECIAL NATURE OF THE HEARTFELT
CEILING PRODUCT, STEPS SHOULD BE TAKEN (BEFORE AND
DURING INSTALLATION, AS WELL AS OVER THE LIFETIME OF THE
CEILING) TO AVOID OR MINIMIZE STATIC AND THE
ACCUMULATION OF DUST, LINT, DIRT OR AIRBORNE PARTICLES
ON OR AROUND THE FELT. HUNTER DOUGLAS DOES NOT
WARRANT AGAINST OR TAKE RESPONSIBILITY FOR ANY SUCH
STATIC OR ACCUMULATION.

*2-3/8" MODULE SHOWN, SEE DETAIL A1.3 FOR AVAILABLE MODULES

INTERIOR INSTALLATION



5015 Oakbrook Parkway, Suite 100
Norcross, GA 30093
T 800.366.4327
F 770.806.0214
HDarchitectural.com

*All rights reserved. This
drawing is the property
of Hunter Douglas. It
may not be copied or
multiplied, neither
wholly nor partly. It may
not be submitted for
perusal to third parties.*

SPECIFICATIONS (unless noted otherwise)

MATERIAL: NON-WOVEN THERMO-FORMABLE POLYESTER
FINISH: 7593F WHITE | 7595F OFF-WHITE | 7596F LIGHT GREY | 7597F MIDDLE
GREY | 7598F DARK GREY | 7599F ANTHRACITE | 7594F BLACK | 7575F CREME |
7576F LIGHT BROWN | 7577F MEDIUM BROWN | 7578F DARK BROWN | 7579F
UMBER
PERFORATION: NOT AVAILABLE

OVERALL ISOMETRIC VIEW

PROJECT: HEARTFELT PRODUCT SPECIFICATIONS
DRAWING NUMBER: HEARTFELT-A1.0
SCALE: AS SHOWN
DRAWN BY: HDA ENGINEERING
DATE: 7/12/18